

## 5. DIMENSIONAL RANGE OF SAVA-VARIOUS SOLID TYRES PRODUCTION PROGRAMME

SIZE ETRTO	RIM ETRTO	PROFILE AND TYPE			DIMENSION (mm)		LOAD CAPACITY (kg) ETRTO					MASS (kg)
		VARIOUS		B19	MAX. WIDTH	OVERALL DIAMETER ±2%	COUNTERBALANCED LIFT TRUCKS (max. 25km/h)		OTHER VEHICLES (TRAILERS) (km/h)			
		CLASSIC	STB	LOAD WHEEL			STEERING WHEEL	6	10	25		
4,00-8	3,00D-8	X			101	411	950	730	950	860	730	11,0
5,00-8	3,00D-8	X			118	458	1415	1090	1415	1285	1090	16,3
15x4 1/2 - 8	3,00D-8	X	X	X	113	377	1040	800	1040	940	800	10,2
16x6-8	4,33R-8	X	X		155	415	1270	975	1270	1150	975	17,2
18X7-8	4,33R-8	X	X		147	455	2145	1650	2145	1945	1650	20,5
6,00-9	4,00E-9	X	X		146	523	1885	1450	1885	1710	1450	25,4
21X8-9	6,00E-9	X			175	515	2755	2120	2755	2505	120	32,0
6,50-10	5,00F-10	X	X		146	574	2340	1800	2340	2125	1800	32,8
7,50-10	5,50F-10	X			171	628	3070	2360	3070	2785	2360	47,3
23X9-10	6,50F-10	X	X		202	586	3355	2585	3355	3040	2585	46,6
200/50-10	6,50F-10	X	X		200	457	2470	1900	2470	2240	1900	24,5
560X165-11	5K-11	X			166	563	2120	1630	2120	1930	1630	33,0
7,00-12	6,00S-12	X	X		165	652	2920	2240	2920	2645	2240	45,2
23X10-12	8,00G-12	X	X		240	580	3770	2900	3770	3420	2900	49
27X10-12	8,00G-12	X	X		243	671	3900	3000	3900	3450	3000	74,4
7,00-15	5,5-15	X			174	728	3545	2725	3545	3215	2725	56,7
7,50-15	6,5-15	X			192	737	3900	3000	3900	3540	3000	65,2
8,25-15	6,5-15	X	X		200	802	4750	3650	4750	4300	3650	83,4
28X9-15	7,0-15	X	X		222	702	3770	2900	3770	3420	2900	63,7
250-15	7,0-15	X	X		215	707	4640	3570	4640	4200	3570	64,5
680X180-15	5K-15	X			183	683	2700	2080	2700	2455	2080	48,7